



Seize the opportunity. Reap the rewards.

Expand your offering, your customer base, and your bottom line with fast-turn, high-margin, wide-format printing.



Seize the high-definition imaging opportunity

- Print 4 color plus white on an extended range of flexible and rigid substrates.
- Increase customer satisfaction with near-photographic images, saturated colors, and smooth gradations with true 8-level, variable-drop grayscale print capability.
- Offer premium-margin applications with industry-leading white ink and single-pass, multilayer printing for greater profit opportunity.

Reap the rewards of UV LED

- Print on more substrates and open doors to more applications and unique creative opportunities.
- Increase uptime and productivity while reducing maintenance with instant on/off LED lamps.
- Drive down operating costs with decreased power use, fewer consumable parts, and less waste with consistent color output and simple operation.

Drive greater gross margins

- Maximize uptime and image quality with a mid-level production printer designed for simple operation and ease of daily use.
- Profit from faster time to customer, dramatically reduced ink use, lower running costs, and high-value specialty substrates.

Features and benefits

- Standard: CMYK plus 2 White channels
- Dynamic curing LED UV lamps
- Up to 458 ft²/hr (42.3 m²/hr)
- Up to 1200 x 600 dpi
- Up to 8 levels of variable-drop grayscale
- Integration ready with EFI™ Web-to-Print and MIS/ERP solutions with native JDF connectivity
- Ships with the EFI Fiery® XF RIP
- RIP and print on demand, or print pre-ripped files at the printer interface
- A choice of ink sets¹:
 - EFI H1625 LED 3M™ ink for a wide range of applications, including those that need to be stretched or heated, or require the 3M™ MCS™ Warranty²
 - POP ink for rigid board printing or applications requiring less ink elongation after cure
- One-year Enhanced Service Program (ESP) warranty covers your printer and Fiery XF software
 - Twelve months of Essential level coverage — 24-business-hour (3-business-day) response

Media/Handling

- Handles flexible and rigid substrates up to 65 in (165 cm) wide and 2 in (5.08 cm) thick
- Image width: 64 in (162.6 cm) full-bleed printing
- Vacuum belt drive system with variable control
- Maximum rigid and roll media weight: 100 lbs (45.4 kg)
- Maximum roll diameter: 9 in (22.9 cm)
- Modular table design for scalable rigid printing depth

¹ The EFI H1625 LED 3M™ and POP inks are NOT top loadable and require a simple change-over kit to move from one ink set to the other.

² The 3M™ MCS™ Warranty backs graphics printed with 3M co-branded ink and select 3M flexible media, printed and applied according to 3M product and instruction bulletins. See www.3Mgraphics.com/warranties to register and for more details.

Resolution

- 300 x 300 dpi, 8 levels of grayscale
- 600 x 600 dpi, 4 and 8 levels of grayscale
- 900 x 900 dpi, 4 and 8 levels of grayscale
- 1200 x 600 dpi, 8 levels of grayscale

Productivity

- Ultra Quality Mode 80 ft²/hr (7.4 m²/hr)
- High Quality Mode 133 ft²/hr (12.4 m²/hr)
- Quality Mode 247 ft²/hr (23 m²/hr)
- Express Mode 458 ft²/hr (42.3 m²/hr)
- White printing, one-half CMYK speeds

Formats

- All popular desktop files formats, including PostScript® 3™, EPS, TIFF, PDF, and RGB/CMYK

Environmental considerations

- Temperature: 65 °F to 80 °F (18 °C to 26.7 °C)
- Humidity: 20% to 80% (noncondensing)
- Weight: 2,722 lbs (1,235 kg), including tables and rollers
- Dimensions (WxDxH) with one set of tables: 137 in (348 cm) x 88 in (224 cm) x 64 in (163 cm)
- Depth: 36 in (91 cm) without tables or rollers, 54 in (137 cm) without tables
- Electrical: 208-240 VAC, single phase, 50/60 Hz, 30 Amps

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalized documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, InkIntensity, Inkware, Jettrion, the Jettrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-White-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.